

Data Sheet

ORCHIDEA Light

Single opening for brick wall

Finished wall thickness 125 mm

Code	Passage size		Overall dimension (B x H) cm	Cassette dimensions (C x H) cm	Inside dimension D cm	Door (Lp x Hp x Sp*) cm
	A cm	H cm				
Dx 91025466 Sx 91025465	60	200	133 x (H+9)	66,3 x (H+9)	6,5	61,5 x (Hp) x 5,0
Dx 91025476 Sx 91025475	70	200	153 x (H+9)	76,3 x (H+9)	6,5	71,5 x (Hp) x 5,0
Dx 91025486 Sx 91025485	80	200	173 x (H+9)	86,3 x (H+9)	6,5	81,5 x (Hp) x 5,0
Dx 91025496 Sx 91025495	90	200	194 x (H+9)	96,3 x (H+9)	6,5	91,5 x (Hp) x 5,0
Dx 91025416 Sx 91025415	100	200	214 x (H+9)	106,3 x (H+9)	6,5	101,5 x (Hp) x 5,0

Code	Passage size		Overall dimension (B x H) cm	Cassette dimensions (C x H) cm	Inside dimension D cm	Door (Lp x Hp x Sp*) cm
	A cm	H cm				
Dx 91025566 Sx 91025565	60	210	133 x (H+9)	66,3 x (H+9)	6,5	61,5 x (Hp) x 5,0
Dx 91025576 Sx 91025575	70	210	153 x (H+9)	76,3 x (H+9)	6,5	71,5 x (Hp) x 5,0
Dx 91025586 Sx 91025585	80	210	173 x (H+9)	86,3 x (H+9)	6,5	81,5 x (Hp) x 5,0
Dx 91025596 Sx 91025595	90	210	194 x (H+9)	96,3 x (H+9)	6,5	91,5 x (Hp) x 5,0
Dx 91025516 Sx 91025515	100	210	214 x (H+9)	106,3 x (H+9)	6,5	101,5 x (Hp) x 5,0

*Sp = maximum thickness recommended

